

THK

Thile totem



Created specifically for prestigious locations such as banks, museums, hotels, malls or meeting rooms the Totem THK is the right compromise between Design and dimensions: available in single-sided version and only 12 cm for a double sided totem with professional high quality LCD monitors equipped with USB auto playback system for streaming videos and images without any external player or software. No screws in sight, with all frontal 6 mm glass, double closure for security and anti-vandalism with an infinite amount of colors and finishes.

All totems can be equipped with touch screen capability with 2 or 40 ultra-fast and sensitive touch, transforming it into an effective wayfinding solution or information point for hospitals and fairs or as a welcome system for companies or hotels.

ENVIRONMENT

Indoor
IP20 (Nema 1) water/dust proof
IK04 vandal proof
Temperature range from 0°C to +40°C

STRUCTURE

Power painted steel
6mm tempered all frontal glass
Slim design
Safety Lock and invisible screws and hinges

TECHNOLOGY AND USAGE

USB auto playback
24/7 usage
Room for external player
PCAP touch available
Small Footprint

AVAILABLE SIZES

portrait

32" 43" 55" 65" 75"

landscape

43"



For more information visit www.fida.it

Copyright © 2022 Fida srl

	THK.P32	THK.P43	THK.L43	THK.P55	THK.P65	THK.P75
--	---------	---------	---------	---------	---------	---------

General

Screen orientation	Portrait	Portrait	Landscape	Portrait	Portrait	Portrait
Screen size (inch)	32"	43"		55"	65"	75"
Screen active area (cm)	69,8 x 39,2	69,8 X 39,2		52,9 X 94,1	80,3 x 142,8	92,8 x 164,9
Display brightness (nit)	400	500		500 / 700 (opt)	500 / 700 (opt)	500 / 700 (opt)
Screen resolution (pixel)	Full HD - 1920x1080	UHD - 3840x2160		UHD - 3840x2160	UHD - 3840x2160	UHD - 3840x2160
Contrast ratio (typ)	1100:1 (typ)	1100:1 (typ)		1100:1 (typ)	1100:1 (typ)	1100:1 (typ)
Viewing angle (H/V)	178° / 178°	178° / 178°		178° / 178°	178° / 178°	178° / 178°
Backlight Life Cycle	50.000 hours	50.000 hours		50.000 hours	50.000 hours	50.000 hours
System operation	24/7/365	24/7/365		24/7/365	24/7/365	24/7/365
Screen side	Single and Double	Single and Double		Single and Double	Single and Double	Single and Double

Environment

Environment protection	Indoor IP20 (Nema 1)	Indoor IP5x (only monitor)		Indoor IP5x (only monitor)	Indoor IP5x (only monitor)	Indoor IP5x (only monitor)
Sun exposure	not allowed	not allowed		not allowed	not allowed	not allowed
Operating temperature	0°C / +40°C	0°C / +40°C		0°C / +40°C	0°C / +40°C	0°C / +40°C
Environment humidity	10% - 80%	10% - 80%		10% - 80%	10% - 80%	10% - 80%
Antivandal protection	IK04	IK04		IK04	IK04	IK04

Enclosure

Air cooling system	passive dissipation	passive dissipation		passive dissipation	passive dissipation	passive dissipation
Enclosure material	Painted Steel	Painted Steel		Painted Steel	Painted Steel	Painted Steel
Glass	Tempered glass (6mm)	Tempered glass (6mm)		Tempered glass (6mm)	Tempered glass (6mm)	Tempered glass (6mm)
Glass reflection	--	--		--	--	--
Standard enclosure color	Black (RAL 9004)	Black (RAL 9004)		Black (RAL 9004)	Black (RAL 9004)	Black (RAL 9004)
Standard glass color	Black (RAL 9005)	Black (RAL 9005)		Black (RAL 9005)	Black (RAL 9005)	Black (RAL 9005)

Power

Vac supply	230V AC +/- 10	230V AC +/- 10		230V AC +/- 10	230V AC +/- 10	230V AC +/- 10
Power consumption (typ)	60 W (single side) 120 W (double side)	80 W (single side) 160 W (double side)		115 W (single side) 230 W (double side)	135 W (single side) 270 W (double side)	185 W (single side) 370 W (double side)

Dimensions

Height (cm)	180	190		210	209	225
Width (cm)	47	60	100	75	95	105
Depth (cm) [Double Sided]	12 - [12]	12 - [12]		12 - [12]	15 - [15]	18 - [18]
Weight (Kg) [Double Sided]	62 - [84]	85 - [103]	125 - [145]	116 - [156]	142 - [210]	195 - [240]
Notes	Built-in Speakers 10Wx2	Built-in Speakers 10Wx2		Built-in Speakers 10Wx2	Built-in Speakers 10Wx2	Built-in Speakers 10Wx2

main OPTIONS

- PCAP Touchscreen
- Camera
- PC / Media player
- Client Logo