

# TKI

## Tactive infokiosk



Tactive TKI is a multifunctional interactive info kiosk, particularly suitable for replacing traditional static lecterns and gives increased vitality to the information since you can easily consult digital brochures, catalogs, videos and interactive multimedia content. But also suggested for queue management systems and as an entry-level terminal for self-ordering applications. Available in 22" and 32", vertical or horizontal. Its elegance can be seen in the details of the vertical column made in an extremely compact and stable metal base that ensures accessibility for the disabled. The frontal door allows for immediate access to the internal devices in order to perform simple and fast maintenance operations.

### ENVIRONMENT

Indoor  
IP20 (Nema 1)  
IP20 (Nema 1) dust proof  
Temperature range from 0°C to +40°C

### STRUCTURE

Structure in steel  
Frontal door for easy operations  
Ergonomic design for disabilities  
Fully customizable

### TECHNOLOGY AND USAGE

250/500 nit brightness  
24/7 usage  
Primary brand PRO grade LCD  
PCAP touch as standard  
Front panel for device integration

### AVAILABLE SIZES

portrait

22" 27"

landscape

22" 27" 32"



For more information visit [www.fida.it](http://www.fida.it)

Copyright © 2023 Fida srl

	TKI.P22	TKI.L22	TKI.P27	TKI.L27	TKI.L32
--	---------	---------	---------	---------	---------

## General

Screen orientation	Portrait	Landscape	Portrait	Landscape	Landscape
Screen size (inch)	<b>21,5"</b>		<b>27"</b>		<b>32"</b>
Screen active area (cm)	26,8 X 47,6		34 X 60		69,8 X 39,2
Display brightness (nit)	<b>525</b>		<b>425</b>		<b>500</b>
Screen resolution (pixel)	Full HD - 1920x1080		Full HD - 1920x1080		Full HD - 1920x1080
Contrast ratio (typ)	1000:1 (typ)		1000:1 (typ)		3000:1 (typ)
Viewing angle (H/V)	178° / 178°		178° / 178°		178° / 178°
Backlight Life Cycle	50.000 hours		50.000 hours		50.000 hours
System operation	24/7/365		24/7/365		24/7/365
Screen side	Single		Single		Single
Touchscreen	PCAP 10P		PCAP 10P		PCAP 12P

## Environment

Environment protection	Indoor - IP20 (Nema 1)		Indoor - IP20 (Nema 1)		Indoor - IP20 (Nema 1) IP54 front
Sun exposure	not allowed		not allowed		not allowed
Operating temperature	0°C / +40°C		0°C / +40°C		0°C / +40°C
Environment humidity	10% - 80%		10% - 80%		10% - 80%
Antivandal protection	--		--		Antivandal glass

## Enclosure

Air cooling system	passive dissipation		passive dissipation		passive dissipation
Enclosure material	galvanized steel		galvanized steel		galvanized steel
Glass	standard		standard		Scratch-free glass (2mm)
Glass reflection	--		--		Antiglare
Standard enclosure color	White (RAL9010)		White (RAL9010)		White (RAL9010)
Standard glass color	Black (RAL 9005)		Black (RAL 9004)		Black (RAL 9005)

## Power

Vac supply	230V AC +/- 10		230V AC +/- 10		230V AC +/- 10
Power consumption (typ)	50 W		60 W		70 W

## Dimensions

Height (cm)	130	122	140	132	130
Width (cm) [Base]	32 [50]	53 [50]	39 [50]	62 [50]	78 [50]
Depth (cm)	40	40	40	40	40
Weight (Kg)	30	30	32	32	38
Notes					

