


# TACTIVE

## TKI InfoKiosk



Tactive TKI is a multifunctional interactive infokiosk, particularly suitable for replacing traditional static lecterns and gives increased vitality and momentum, since you can easily consult digital brochures, catalogs, video and interactive multimedia content. It is available in 22" and 32" LCD 10 touch touch screen, vertical and horizontal. Its elegance can be seen in the details of the vertical column made in extremely compact and stable metal base that ensures accessibility for the disabled. The rear compartment can be inspected and allows for immediate access to the internal devices in order to perform simple and fast maintenance operations.




### Major Features

- ERGONOMIC DESIGN
- READY FOR THE DISABLED
- FULLY CUSTOMIZABLE
- FRONT PANEL FOR DEVICE INTEGRATION
- SMALL FOOTPRINT
- LANDSCAPE/PORTRAIT DISPLAY ORIENTATION
- PCAP TOUCH AS STANDARD
- 24/7 USAGE

### STRUCTURE AND MATERIALS

- Structure in steel
- Scratch-free and reflective glass 4mm
- Back door for easy maintenance
- Ergonomic design for disabilities
- Safety Lock and invisible screws and hinges
- Custom frontal panel for various devices such as Printers and Card Reader


### DISPLAY SIZES



### OPTIONS

● Available ● Not Available ● Included ● On project

|              |                     |              |         |          |                     |               |                  |                    |                      |
|--------------|---------------------|--------------|---------|----------|---------------------|---------------|------------------|--------------------|----------------------|
|              |                     |              |         |          |                     |               |                  |                    |                      |
| CUSTOM COLOR | AUDIO 2X5W          | TOUCH SCREEN | UMTS-4G | WI-FI    | BLUETOOTH           | WEBCAM        | MEDIA PLAYER     | CARD READER        | BARCODE READER       |
|              |                     |              |         |          |                     |               |                  |                    |                      |
| YOUR LOGO    | PROXIMITY IR SENSOR | SHOCK SENSOR | HVAC    | SOFTWARE | ADVANCED DIAGNOSTIC | BASE + WHEELS | CASHLESS PAYMENT | A4 THERMAL PRINTER | 80mm THERMAL PRINTER |



## TECHNICAL SPECIFICATIONS



General

| Product code              | TKI.P22<br>(Portrait)         | TKI.L22<br>(Landscape)  | TKI.L32<br>(Landscape)        |
|---------------------------|-------------------------------|-------------------------|-------------------------------|
| Screen size (inch)        | 22"                           |                         | 32"                           |
| Screen active area (cm)   | 26,8 X 47,6                   |                         | 69,8 X 39,2                   |
| Display brightness (nit)  | 215                           |                         | 460                           |
| Backlight technology      | LEDedge                       |                         | LEDedge                       |
| Screen resolution (pixel) | Full HD - 1920x1080           |                         | Full HD - 1920x1080           |
| Contrast ratio            | 3000:1 (typ)                  |                         | 3000:1 (typ)                  |
| Viewing angle (H/V)       | 178° / 178°                   |                         | 178° / 178°                   |
| Backlight Life cycle      | 50.000 hours                  |                         | 50.000 hours                  |
| System operation          | 24/7/365                      |                         | 24/7/365                      |
| Screen orientation        | Portrait                      | Landscape               | Landscape                     |
| Screen side               | Single                        |                         | Single                        |
| Interactive touch         | Projected capacitive 10t      |                         | Projected capacitive 30t      |
| Environment rating        | Indoor<br>IP20 (Nema 1)       | Indoor<br>IP20 (Nema 1) | Indoor<br>IP20 (Nema 1)       |
| Operating temperature     | 0°C / +40°C                   |                         | 0°C / +40°C                   |
| Environment humidity      | 10% - 80%                     |                         | 10% - 80%                     |
| Antivandal protection     | n.a.                          |                         | n.a.                          |
| Air cooling system        | n.a.                          |                         | n.a.                          |
| Standard color            | As shown below                |                         | As shown below                |
| Enclosure material        | Steel                         |                         | Steel                         |
| Glass                     | Scratch-free glass<br>(1,5mm) |                         | Scratch-free glass<br>(1,5mm) |
| Glass reflection          | Anti-reflection               |                         | Anti-reflection               |
| Vac supply                | 230V AC +/- 10                |                         | 230V AC +/- 10                |
| Power consumption (Typ)   | 50W                           |                         | 70W                           |
| Height (cm)               | 128                           | 120                     | 130                           |
| Width (cm)                | 33                            | 53                      | 78                            |
| Depth (cm)                | 46                            | 40                      | 42                            |
| Weight (Kg)               | 35                            | 40                      | 50                            |
| Base dimensions (cm)      | 33(W)x1(H)x40(D)              | 53(W)x1(H)x40(D)        | 78(W)x1(H)x40(D)              |

Environment

Enclosure

Dimensions



## STANDARD COLORS AND FINISHING

Enclosure Colors ● Black RAL 9005  
○ White RAL 9010  
■ On request

Glass Colors ● Black RAL 9005  
■ On request

## TESTS AND CERTIFICATIONS

LVD 2014/35/UE  
EMC 2014/30/UE  
ROHS 2011/65/UE  
IP Code IEC 60529  
IK Rating IEC 62262

Safety of Information Technology Equipment:  
IEC 60950-1  
Safety Requirements of Audio, Video and Similar  
Electronic Apparatus: IEC 60065

